

Bedding in Procedure

To ensure perfect functioning and to achieve the maximum longevity of your EXEDY Racing Clutch, EXEDY Clutch Europe Ltd. recommends that the clutch is allowed to “bed in” correctly immediately after installation. This will ensure the friction surfaces of the components are correctly aligned and mated for future use.

Our recommendation is to perform positive and accurate gear changes in the low to mid rev range for the first 500 miles of driving with the new clutch installed. This should be carried out during city type driving, or as normal driving as possible depending on the circumstances. Certainly, racing starts and quick shifting should be avoided during the “bedding in” stage.

Understandably, this will not be possible in certain situations, especially when racing or rallying, for example. However, whenever it is possible or practical, “bedding in” the clutch correctly will pay future dividends in operational efficiency and product longevity.

Furthermore, the modern materials used in the manufacture of our product range mean it is absolutely never necessary or advised to slip the clutch in order to “bed it in”. Induced clutch slip will result in premature degradation of the friction material, ultimately leading to greatly reduced product lifespan.

If you require any further information or assistance on this subject, please use the contact information below.

Issued: 26/02/2013 SGC

EXEDY Clutch Europe Ltd
Unit 2, Rokeby Court, Runcorn, Cheshire, WA7 1RW
Tel: +44 (0) 1928 571850 Fax +44 (0) 1928 571852 E-mail: technical@exedy.co.uk
©EXEDY Clutch Europe Ltd | www.exedy.co.uk

