

Slow Speed Continuous Lifting of Grains

BUCKET ELEVATOR

SEC6.7.8S-T / SE5.6.7.8.10S-T



Specifications

Model		SEC6S-T	SEC7S-T	SEC8S-T	SE5S-T	SE6S-T	SE7S-T	SE8S-T	SE10S-T		
Output Capacity (t/h)	Brown rice or Milled rice	6	10	15	6	10	20	30	50		
Output Capacity (VII)	Cleaned paddy	-		-	4	6	12	20	30		
Revolution (rpm)	Revolution (rpm)					145	105	95	90		
Peripheral speed (m/min)	Peripheral speed (m/min)					80 88		105	130		
Belt width (inch)	Belt width (inch)					6	7	8	10		
Belt used	Belt used					Fuel oil A resistance flat belt, Oil resistance flat belt (White)					
Bucket Capacity (ℓ)		1.0	1.5	2.7	0.3	0.5	0.8	1.3	2.5		
Pitch of buckets (mm)	Pitch of buckets (mm)				155	180	190	230	260		
Dimension length (mm)		4,800~13,700	5,000~14,800	6,000~15,000	4,726~13,266	4,891~15,871	5,096~16,076	5,385~30,095	5,695~30,405		
Transmission unit (Geared motor)	He s	0.4kW 1/20 0.75kW 1/20	0.4kW 1/20 0.75kW 1/20 1.5kW 1/20 2.2kW 1/20	0.75kW 1/45 1.5kW 1/45 2.2kW 1/45 3.7kW 1/45	0.4kW 1/10	0.4kW 1/10 0.75kW 1/10	0.75kW 1/15 1.5kW 1/15 2.2kW 1/15	1.5kW 1/15 2.2kW 1/15 3.7kW 1/15	2.2kW 1/15 3.7kW 1/15 5.5kW 1/15		
Net weight (kg)		1	-	-	(E)	7,		-	521		

^{*} SESS-T and SE6S-T are belt-driven. SE7S-T, SE8S-T and SE10S-T are chain-driven. *Specifications are subject to change without notice.

For the vertical lifting of bulk materials. Satake's bucket elevator is unsurpassed.

FEATURES:

1. Easy conveying of grains

A bucket elevator of the belt type is both highly economical and most suitable for grains which are relatively easily transported.

2. Multi-way parts

A multi-way valve or distributor may be attached near or away from the

A hopper can also be installed on either side of the elevator.

3. User-friendly equipment

Belt tension is maintained in its optimum condition by means of the spring tensioner in the upper elevator. Buckets are capable of continued running even during periods of accidental overflow.

Rotation sensor and backstop can be also supplied as options - ensuring safe operation.

Dimensions

(SEC)

П 0

K(K)


Selections

SEC Guided Discharge Type



Effective discharge of materials makes use of bucket undersides Quantity of broken materials during conveying can be minimized.

SE Centrifugal Discharge Type



Discharge of materials by centrifugal power. Suitable for high capacity use.

Model	Α	В	B'	С	D	Е	F	G	Н	1	J	K	K'	L
SEC6S-T (mm)	200000-00	-C-116-C-45	27740000000	Charles Control	10-11-11-11	The Victory	2010/05/06	***********	Harris Control of	2000000		G114245000	recovered rates in	with window: 1830. Middle section without
SEC7S-T (mm)	730	260	250	615	805	680	260	1,020	360	215	170	770	1,005	
SEC8S-T (mm)														

* (K') shows the height of 400 square hoppers pecifications are subject to change without notice

Model	Α	В	B'	С	D	E	F	G	Н	1	J	K	L
SE5S-T (mm)	520	189	180	430	635	560	180	760	265	180	180	647	Middle section
SE6S-T (mm)	620	220	210	530	762	560	220	820	265	195	195	719	with window: 1,830.
SE7S-T (mm)	730	259	250	615	805	680	260	1,020	355	220	220	962	Middle section
SE8S-T (mm)	970	292	280	765	950	775	310	1,275	505	200	200	1,025	without window:
SE10S-T (mm)	1,140	342	330	936	1,105	905	335	1,495	550	225	225	1,140	1,830, 910, 610.

^{*}Dimensions are subject to change without notice.

All copyright and trademark rights of this catalog belong to Satake Co., unless otherwise noted. Unauthorized copying, reprinting, etc. are forbidden. All Satake products are the subject of continuous development and, as a result, their specification may change and differ in detail from those shown.

SATAKE USA INC.

SATAKE CORPORATION

Head Office

2-30 Saijo Nishihonmachi, Higashi-Hiroshima-shi, Hiroshima-ken, 739-8602, Japan URL: https://satake-group.com/

SATAKE INDIA ENGINEERING PVT. LTD. 4th Floor, Tower-1, HB Twin Towers, A2, 3, 4, Netaji Subhash Place, Wazirpur District Centre, New Delhi, 110034, India URL: www.satakeindia.com

SATAKE MANUFACTURING (SUZHOU) CO., LTD.

229 Jin Feng Road, Suzhou New District, Suzhou City, Jiangsu Province, 215129, China URL: www.satake.cn

Korea Branch

Alpha mighty Dunsan Building, 16F, 239, Daedeck-daero, Seo-gu, 35229 URL: https://satake-group.com/

SATAKE (THAILAND) CO., LTD. 133,134 Moo 5, Bangkadi, Mueang Pathum Thani, Pathum Thani 12000, URL: www.sataketh.com

SATAKE AUSTRALIA PTY. LTD.

15 Leland Street, Penrith, N.S.W., 2750, Australia URL: www.satake.com.au

SATAKE ASIA CO., LTD.

10900 Cash Road, Stafford, Texas, 77477, U.S.A. URL: www.satake-usa.com

SAINCE NO. L. L. L. L. SAB/B4 Mahatun Plaza Bld., 8th Floor, Ploenchit Rd., Lumpini, Pathumwan, Bangkok, 10330, Thailand URL: www.sataketh.com

SATAKE AMERICA LATINA LTDA. Rua Xavantes, 155-Pav. 20, Bairro Atiradores, CEP 89203-210, Joinville, Santa Catarina, Brazil URL: www.satake.com.br

PT. SATAKE GOBEL INDONESIA Gedung Surabaya Bumi Mandiri, Lantai 9, Jalan Jenderal Basuki Rachmat Nomor 129-137, Unit 905 B, Indonesia URL: https://satake-group.com/ SATAKE EUROPE LTD. Horsfield Way, Bredbury Industrial Park, Bredbury, Stockport, Cheshire, SK6 2SU,

URL: www.satake-europe.com

SATAKE VIETNAM CO., LTD. Copac Square 12 Ton Dan street, Floor 3A, Ward 13, District 4, HCMC, Vietnam URL: https://satakevietnam.com/

ISO 9001 Certification

ISO 14001 Certification

SATAKE CORPORATION has obtained ISO9001 and ISO14001 certification. These international standards for management systems ensure Satake will continue to provide high quality products and services.

No. 791-01